

# PEINEMANN 5-TLX

The **Peinemann Quintuple Lance Feeder (5-TLX)** from the TLX Series is the lightest, strongest and most versatile tube feeder in the industry. Its NEW modular design is up to 30% lighter while even stronger than before due to an ultra-light carbon fiber drive unit. The interchangeable gear drive system provides 25% additional speed and power control, providing up to 130kg push/pull strength with one motor. This makes the 5-TLX an all-in-one powerhouse. The highly modular design enables quick assembly, tool-free cartridge replacement and easy maintenance.



The 5-TLX can easily be converted into a Single, Dual, Triple or Quadruple Lance feeder. It is ATEX approved and assembled in the Netherlands.

## BENEFITS

**Lightweight components** - The 5-TLX is built with our most-proven components and up to 30% lighter while stronger than ever before. It comes with an ultra-light weight carbon fiber drive unit and corrosion-resistant self-lubricating chains. The improved design enables improved handling and quick assembly.

**All-in-one powerhouse** - The all-NEW gear drive system and powerful Atlas Copco motor convert the 5-TLX into an all-in powerhouse. The 5-TLX comes with two extra gears to increase speed to 125% or decrease speed to 75% on top of standard speed control. Further, the Atlas Copco motor is specially tailored to the 5-TLX and provides up to 130 kg (287 lb) push/pull strength in low gear mode with one motor.

**Highly versatile** - The Peinemann 5-TLX is the most versatile feeder in the industry. Its modular design allows for quick assembly, tool-free cartridge replacement, and easy maintenance. The 5-TLX can easily be converted into a Single Pipe, Dual Lance, Triple Lance or Quadruple Lance feeder.

## FEATURES


- Lightweight components enabling improved handling and quick assembly.
- All-in powerhouse with up to 130 kg (287 lb) push/pull strength in low gear with one motor.
- Durable polyurethane chain blocks with long lifetime.
- Quick assembly, tool-free cartridge replacement and easy maintenance.
- ATEX approved, extensively tested, and assembled in the Netherlands.



INTERCHANGEABLE  
GEAR



DURABLE  
POLYURETHANE



COMPACT INTEGRATED  
AIR MOTORS

## 5-TLX SPECIFICATIONS

General	
Length (drive unit)	46.5 cm (18.3 in)
Width (drive unit)	26.5 cm (10.4 in)
Height (drive unit)	31.5 cm (12.4 in)
Weight (drive unit incl. cartridges and motor)	17 kg (37.5 lb)
Hose feed rate	40 - 70 cm/s (15.7 - 27.6 in/s)
Max. push/pull force	130 kg (287 lb)
Pitch adjustment range	25 - 53 mm (0.98 - 2.09 in)
Motor	
Motor model	Atlas Copco LZB46-ML-AR007-50
Max. output	0.62 kW (0.83 hp)
Min. air pressure	3.0 bar (43.5 psi)
Operating air pressure	6.3 bar (91.4 psi)
Max. air pressure	7.0 bar (101.5 psi)
Max. air consumption	14 l/s (29.7 cfm)
Stall torque	32 Nm (23.3 ft lb)
Vane type	Lubrication free
Hose specifications	
Hose size	3/2 - 5/2
Hose outer diameter	7 - 11.5 mm (0.28 - 0.45 in)
Max. hose coupling diameter	15 mm (0.59 in)

## **ACCESSORIES**


### **TIMBERBOX PNEUMATIC**

The Peinemann Timberbox creates automatic forward/reverse strokes. These oscillating movements allow for improved cleaning and extent nozzle life. The Peinemann Timberbox is attached to the standard remote control.




### **HOSE REEL INDIVIDUAL**

Individual stackable hose reel that is suitable with hose size 3/2 - 8/2. The max. water pressure is 1,500 bar (21,756 psi). A special rear inlet adapter is needed. The hose reel is compatible with a wide range of Peinemann feeders.




## CONVERSION KITS

### SINGLE PIPE SETUP



### DUAL LANCE SETUP



### TRIPLE LANCE SETUP



### QUADRUPLE LANCE SETUP

